

Everply is a smooth exterior masonry coating developed for application to stone, concrete and brick substrates

PURPOSE

Everply is designed to coat the exterior of dwellings constructed of brick, stone and concrete substrates.

METHOD OF APPLICATION

Remove any loose or chalky areas to be treated and prepare any areas affected by mould, algae and fungal growth in the manner described below.

The presence of algae and fungi growth

The substrate should be pre-treated with **Ever**san Sanitising Wash prior to application of the **Everply** system. (See Data Sheet Number 1)

Existing masonry or render

Pre-treatment with **Ever**lac Water Based Stabilising Solution (See Data Sheet 19) is recommended where existing, very porous masonry or render is to be covered.

Timber substrates

Timber substrates should be primed with **Ever**block Stain Blocking Primer prior to application of the **Everply** system to prevent the migration of oils, tannin and adhesive residues. (See Data Sheet Number 2)

General

The application of **Everply** may be carried out using brush, roller or high pressure spray equipment (spray evenly using a two-pass technique) in two coats.

Do not apply to damp surfaces or at temperatures below 5°C.

Subject to the porosity of the substrate the first coat of **Everply** may be thinned by 10 – 20% with white spirit.

SPECIAL PROPERTIES

- Excellent alkali resistance
- Good anti carbonation properties
- Water permeable
- Available in a full range of colours
- Fast drying

TECHNICAL DATA

COLOUR – Available in a comprehensive range of colours.

DRYING AND CURING – Drying times will vary with air movement and temperature. Initial dry should be around 1- 2 hours in good drying condition.

COVERAGE – Coverage will depend on substrate nature, temperature and method of application but typically will be in the order of:

Eversan Sanitising Wash approx. 15m²/ litre

Everlac Stabilising Wash approx. 15m²/ litre

Everblock Stain Blocking Primer approx. 8-12 m²/ litre

Everply 10 - 12m²/litre on smooth surfaces

STORAGE AND SHELF LIFE – 12 Months in original sealed containers in dry conditions. Always store above 5°C

CLEANING EQUIPMENT – Clean tools immediately with white spirit

PACKAGING – 25 litre Metal buckets

FLASHPOINT – 38°C

HEALTH & SAFETY – **Everply** is hazardous and flammable. Strict safety regulations should be adhered to. Goggles and gloves to be worn at all times. Use air fed mask when spraying.

A Material Safety Data Sheet is available on request