

Flexible

Evercoat is a high build water based stucco style textured exterior wall coating designed for application to a wide variety of substrates

PURPOSE

Evercoat HiBuild Flexible is a high build textured product used as an exterior coating on various types of substrates including wood and all forms of masonry surfaces.

METHOD OF APPLICATION

It is essential that faults that allow water to enter the structure e.g. broken rainwater guttering, coping stones etc are repaired before coating.

Algae and fungi should be dealt with, firstly using **Everlac** Biodegradable Exterior Wall Cleaner followed by **Eversan** Sanitising Wash.

Badly loosened render should be replaced however where such looseness is limited the surfaces may be consolidated using **Everlac** Water Based Stabilising Solution before coating.

New wood should be primed before coating using **Everblock**.

Given its excellent alkali resistance, **Evercoat** HiBuild Flexible may be applied directly to new rendering.

Evercoat HiBuild Flexible may be applied by float roller or spray.

Evercoat HiBuild Flexible affords excellent water vapour permeability but at the same time is highly resistant to liquid water.

A variety of surface patterns may be achieved with the help of various textured rollers.

SPECIAL PROPERTIES

- Good water vapour permeability
- Algae and fungi resistant
- Covers defects and variability in substrate
- Long life
- Very Flexible
- Single application
- Easy to apply

TECHNICAL DATA

COVERAGE - Coverage will vary with the thickness applied but will be typically 1m² / litre on smooth surfaces.

DRYING AND CURING - **Evercoat** HiBuild Flexible dries hard and then cures. The full cycle is subject to prevailing climatic conditions i.e. up to 72 hours in winter and within 3 hours in the summer depending on temperature, humidity and air movement.

Evercoat HiBuild Flexible should not be applied when the ambient temperature and/or the temperature of the surface to be coated is below 5°C. Beware of frost in walls.

Curing time will be reduced when the storage and application temperatures are kept below 10°C.

COLOUR - Available in a comprehensive range of colours

STORAGE - Always store above 5°C.

SHELF LIFE - 12 months in original sealed containers in dry conditions.

CLEANING EQUIPMENT - All tools and equipment should be cleaned immediately after use with water. Wipe up spots or splatters before they dry.

PACKAGING - 20 litre plastic buckets

FLASHPOINT - None, water based.

HEALTH & SAFETY - **Evercoat** HiBuild Flexible is non flammable with no measurable flash point.

A Material Safety Data Sheet is available on request.

